


===== WPI =====
 TI - Digital multiplexing screen images of multiple channels in transmitter to provide picture-in-picture display
 AB - J06303543 The television system compresses the voice messages at the transmitting end by encoding them with suitable encoder. Error correcting codes are added to this encoder signal. Similar set of signals from various channels are processed, multiplexed, digitally modulated and transmitted.
 - In the receiver these signals are digitally demodulated. The error correcting codes are then used to ensure identity of the channels. Based on the program chosen by the user, the corresponding encoder image screen is made as the main screen and the remaining small screen. These are stored in temporary memories. The main and small screen images are decoded separately. The main screen image is processed and then displayed on the screen along with the other images.
 - USE/ADVANTAGE - For use in multiple channel television system. Simplifies program selection method of small screen in television receiver, results in presentation of large and small screens simultaneously.
 - (Dwg.1/9)
 PN - JP6303543 A 19941028 DW199503 H04N5/45 012pp
 PR - JP19930085894 19930413
 PA - (HITA) HITACHI LTD
 MC - W03-A11 W03-A13B
 DC - W03
 IC - H04N5/45
 AN - 1995-017976 [03]

BEST AVAILABLE COPY

===== PAJ =====
 TI - DIGITAL TELEVISION BROADCAST RECEIVER AND BROADCASTING SYSTEM
 AB - PURPOSE: To display plural pieces of video information on the same screen simultaneously as plural slave screens without expanding the scale of a demodulation means in a multi-channel digital television broadcast receiver.
 - CONSTITUTION: A transmission side transmits information required for the decoding of information as slave screen information by adding on additional data, or transmits the slave screen as the hierarchical information of a master screen separately from master screen information. A reception side selects plural pieces of compression coding video information at a program selecting means 13, and decodes one of selected information as the master screen information and others as the slave screen information by a master screen video encoder 14A and a slave screen video encoder 14B.
 PN - JP6303543 A 19941028
 PD - 1994-10-28
 ABD - 19950228
 ABV - 199501
 AP - JP19930085894 19930413
 PA - HITACHI LTD
 IN - NODA MASAKI; others: 03
 I - H04N5/45



<First Page Image>